



GETICA CCS CO₂ CAPTURE

CO₂ Transport and Storage

“Natural Gas Knowhow Centre in Mediaș”, Thursday, 9th June 2011

Lavinu DANCIU, Development and Strategies Department Director, Turceni Energy Complex
Gianluca DI FEDERICO, Business Sales Manager, Alstom Carbon Capture GmbH



Institutional
and Financial
Support



Project
Company



Tehcnical
Consortium



Support
Services



Turceni Power Plant (1)

- ✓ Pulverized lignite-fired Power Plant
- ✓ Conventional steam cycle in condensation
- ✓ Operates in the base load of the National Grid
- ✓ Its seven power units were commissioned in 2 stages:
 - ✓ Stage I – 4 units (no. 1 – 4) of 330 MWe = 1320 MWe, commissioned between 1978 - 1982
 - ✓ Stage II – 3 units (no. 5 – 7) of 330 MWe = 990 MWe, commissioned between 1983 – 1987; the construction of the Power Unit no. 8 was stopped by Governmental Decision, HGR no. 897/2002.





Institutional
and Financial
Support



Project
Company



Tehnic
Consortium



Support
Services



Turceni Power Plant (2)

- ✓ The present situation of the power units (the commissioning year between brackets):
 - ✓ Unit no. 1 (1978): in operation
 - ✓ Unit no. 2 (1979): out of service, decommissioning started
 - ✓ Unit no. 3 (1980): in operation
 - ✓ Unit no. 4 (1981): in operation, retrofitted in 2002
 - ✓ Unit no. 5 (1983): in operation, retrofitted in 2006
 - ✓ **Unit no. 6 (1985): conserved, will be retrofitted**
 - ✓ Unit no. 7 (1987): in operation
 - ✓ Unit no. 8 (unfinished): decommissioned





Turceni – Unit no. 6 (330MW)

- undergoing retrofitting process – deadline 2014
- FGD system – deadline 2012
- ash and slag “dense slurry” system – deadline 2012

Main technical features after retrofitting

Steam Turbine + Electric generator

Rated gross power	330MW
Maximum long term available gross power	310MW
Annual average gross power	280MW

Steam Boiler

Steam flow	1035t/h
Steam parameters (pressure / temperature)	192 / 540 bar / °C
Efficiency	88%





Chilled Ammonia Process



Well-known and reliable flow-scheme:

- ✓ Cooled flue gas is treated with ammonium carbonate in solution, which reacts with CO₂ to form ammonium bicarbonate.
- ✓ Raising the temperatures reverses the above reactions – releasing pressurized CO₂.

Advantages over traditional technologies:

- ✓ Energy-efficient capture of CO₂.
- ✓ High CO₂ purity, high CO₂ pressure.
- ✓ Tolerant to oxygen and flue gas impurities.
- ✓ Stable reagent (no degradation possible).
- ✓ No emission of trace contaminants.
- ✓ Low-cost and globally available reagent.
- ✓ Value by-product (fertilizer).



Ad-hoc technology!



Institutional
and Financial
Support



Project
Company



Tehcnical
Consortium



Support
Services



Chilled Ammonia Process Mountaineer Validation Facility – New Haven

- ✓ AEP's Mountaineer Plant (1,300 MWe) - coal fired (West Virginia).
- ✓ In 2009 CAP applied to a slip-stream of flue gases (20 MWe).
- ✓ CO₂ stored into deep formations (1.5 miles beneath plant surface).
- ✓ Validation Plant (Mountaineer) – final results:
 - ✓ CO₂ Captured = 7,000 tons/month.
 - ✓ CO₂ Capture Rate: 90% demonstrated (75% as design).
 - ✓ CO₂ Stream Purity of 99% minimum.
 - ✓ Ammonia losses in line with predictions / simulations.
 - ✓ Energy Penalties in line with predictions / simulations.
 - ✓ Capture Plant availability greater than 90%.
 - ✓ Robust steady operation during all operation modes.
- ✓ Plant will run till June 30th 2011 to further investigate storage.
- ✓ ALSTOM gained important expertise **in the full CCS chain**.
- ✓ Important contribution to implementation of risk mitigation and management.



Mountaineer Power Plant





Feasibility Study Results

- ✓ Technology Selection (Chilled Ammonia Process).
- ✓ Process Optimization (lower parasitic load to power plant).
- ✓ Heat Integration Concept selected (CCS Ready Concept).
- ✓ OPEX and CAPEX estimated.
- ✓ Identification of interfaces with Power Plant.
- ✓ Identification of interfaces with Transport / Storage.
- ✓ Preliminary 3D Model for the new plant.
- ✓ Characterization of CO₂ Stream delivered to Transport.
- ✓ NER300 Application, support for its preparation (workshop).



Institutional
and Financial
Support



Project
Company



Tehnic
Consortium



Support
Services





Conclusions

- ✓ Chilled Ammonia Process was selected due to the higher performances and negligible environmental impact (legislation compliance and no harmful effluent).
- ✓ Chilled Ammonia Process has been validated in accordance with Alstom's R&D Roadmap (one further step to commercial size plants).
- ✓ Chilled Ammonia Process has demonstrated a robust steady-state operation (even at load changes) using real flue gas.
- ✓ Process simulations have been proved to be reliable and predicting well the actual plant parameters, such as:
 - ✓ CO₂ Capture Rate
 - ✓ Ammonia Losses
 - ✓ Energy Demand
 - ✓ Solution Circulation Rate
 - ✓ CO₂ Composition
- ✓ Confidence in the design for a large-scale demonstration project.
- ✓ Next step → FEED to be developed to reach +/- 10% cost estimation before EPC.



Institutional
and Financial
Support



Project
Company



Tehnicl
Consortium



Support
Services



Institutional
and Financial
Support



Project
Company



Tehcnical
Consortium



Support
Services



**WE STAND FOR THE DEVELOPMENT
OF CCS PROJECTS IN ROMANIA**



Thank you for your attention!

Lavinu DANCIU

E-mail: lavinu.danciu@eturceni.ro

Gianluca DI FEDERICO

E-mail: gianluca.difederico@power.alstom.com

